

The Monoblock Amplifier CX is the next evolution in the Coda C Series of amplifiers. The CX brings together the best design topologies from our many amplifiers, regardless of pricepoint, and combines them with the 6th generation of our most popular Coda and OEM amplifier. The result is a breathtaking achievement that many have called our best effort to date.

The Monoblock CX and Stereo CSX Amplifiers are the first fruits of our 2 year "X" series development project and represent a defining example of superior sonics, attractive style, logical ergonomics, and robust engineering.



- State of the art high current monoblock amplifier in an elegant hand-crafted chassis
- Fully balanced design utilizing a discrete FET differential input, VMOSFET voltage gain stage stage DC coupled to a non-bridged ultra wideband bipolar output stage
- Coda's "Precision Bias" technique yields a seamless transition from Class A operation regardless of the complexity of the load impedance.
- Very high linear damping
- AC-coupled unbalanced input and true DC-coupled balanced input
- Gold plated FR-4 glass epoxy printed circuit boards
- Wideband, fully-regulated power supply with EMI and RFI line filtering and low impedance filter capacitor array
- Left and right channel status indicators
- WBT Topline Binding Posts and RCA Connectors
- Silver/Copper based Lead Free solder exclusively
- Carefully selected and evaluated audiophile grade parts, rigorously tested using both objective & subjective techniques
- Enhanced styling with graphite anodize & stainless steel accents to match Coda 05X, 06X and CLX preamplifiers

Rated Power:	450W into 8 Ohm Load 900W into 4 Ohm Load 1 Ohm Load Stable Class A operation to 50W
Bandwidth:	5 Hz to 100 kHz
Distortion	.03% from 10Hz to 20kHz driven into 4 to 8 ohm loads
Amplifier Gain:	26db
Maximum Current:	>150 Amperes peak
Noise:	>-100 dBA referenced to 1 Volt output
Slew Rate:	>50 Volts per microsecond
Damping Factor:	>250
Input Impedance:	50k Ohms unbalanced 1k Ohms balanced
Power Supply:	3.0 kVA toroidal transformer, high speed rectifiers and 80,000uf capacitance.
Dimensions:	17" W x 14" D x 5.5" H
Weight:	65 lbs.
Warranty:	10 years